DFP450W Digital Pocket Test

The DFP450W Digital Pocket Test with Adjustable Temperature Alarm was specifically designed for the harshest foodservice environments. Instrument can be programmed to provide a visual alarm (blinking display) once the set temperature is reached. The

initial default alarm temperature is 140°F (60°C).



No "Field" Adjusting of Calibration Settings

No Risk of Introducing Error into the Instrument




Specifications

- Temperature Range: -40° to 450°F (-40° to 232°C)
- Accuracy: ±2°F from 0° to 350°F (±1°C from -18° to 177°C), ±4°F from -40° to 0°F (± 1.5 °C from -40° to 18°C) and ± 4 °F from 350° to 400°F (±1.5°C from 177° to 204°C)
- Resolution: Tenth Degree (0.1°)
- LCD: Larger 0.375" (9.5 mm) H x 0.8125" (20.6 mm) W* Display
- Waterproof
- With Anti-microbial Additive*
- Adjustable Preset Temperature Alarm*
- Min*/ Max / Hold* Modes
- Used to Test Dishwasher Rinse Temperatures
- 4.75" / 120 mm Stainless Steel Stem
- Reduced tip for <6 Second Response Time*
- Protective Sheath & Pocket Clip
- Auto Off after 10 Minutes
- Low Battery Indicator*
- 1.5v #LR44 Battery & Spare included
- CE Marked, NSF Listed
- Guaranteed Accurate for Life*
- Lifetime Warranty

LIFETIME WARRANTY INCLUDES CALIBRATION ACCURACY: Any AfL designated instrument which proves to measure temperatures out of the specified accuracy range or be defective in material or workmanship will be replaced without charge upon receipt of the unit prepaid.

- Individual Clamshell Package Weight: 2.5 oz. (71 grams)
- Package Dimensions: 9.375" x 4.875" x 1.125" (238 x 124 x 29 mm)
- Package Cube: 0.3
- Six (6) per Shelf Box, 36 per Master Carton





Potentially hazardous mercury thermometers are often used to check the extreme water temperature of commercial dish water. Eliminate the risk of a mercury spill; the DFP450W stores the maximum heat registered and is waterproof.



Eliminate Error - Remove Risk