


## FEATURES

- 0.1 mA Current Resolution.
- True RMS Measurement For All Applications.
- Backlight Function.
- Peak Hold Measurement Function.
- Data Hold Function.
- Zero Function.
- Auto Power Off.
- Autoranging.

## GENERAL SPECIFICATIONS

- **Numerical Display:**  
4 digital liquid crystal(LCD), Maximum reading 5000.
- **Low Battery Indication:** The  is displayed.
- **Sampling Rate:** 2 Times/sec
- **Power Source:** 1.5V size AAA battery x 2
- **Auto Power Off:** 30 minute.
- **Operating Temperature and Humidity:**  
0°C to 40°C(32°F to 104°F); < 80%RH
- **Storage Temperature and Humidity:**  
-10°C to 60°C(14°F to 140°F); < 80%RH
- **Jaw Opening Diameter:** 23 mm
- **Dimensions/ Weight:** 206(L)×76(W)×33.5(H)mm/ Approx.270g
- **Accessories:**  
Carrying Case, Batteries, Test Lead, Instruction Manual.

★ 0.1 mA!



LED Back Light



## ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
DCA	500.0mA/5000mA/10.00A	0.1mA/1mA/0.01A	±1.8%rdg ±5dgts
ACA	500.0mA/5000mA/20.00A	0.1mA/1mA/0.01A	±1.8%rdg ±5dgts
DCV	50V/300V	0.01V/0.1V	±1%rdg ±2dgts
ACV	50V/300V	0.01V/0.1V	±1%rdg ±5dgts
Ohm	500/5K/50K/500KΩ	0.1Ω/1Ω/10Ω/100Ω	±1%rdg ±2dgts
•))	< 120Ω		

\*The specifications and other information in this catalogue are subject to change without prior notice.

**CENTER**<sup>®</sup>  
**CENTER TECHNOLOGY CORP.**

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,  
New Taipei City 238, Taiwan  
TEL: 886-2-26763926 E-Mail: center@centertek.com  
FAX: 886-2-26763925 http://www.centertek.com

Distributed by: