



STANDARD CONSTRUCTION

- RTD, Band 1 element, 3 wire construction
- Length up to 200mm in increments of 50mm
- Rated to 125°C
- No process fitting

ADDITIONAL REQUIREMENTS

- If variations from the standard construction are required please specify. Options include:
- Band 5 element
 - 4 wire construction
 - 4 to 20 mA OUTPUT

.	2	
.	1	
Date	0	ORIGINAL ISSUE

APP	JW	12/05/09	STANDARD TOLERANCES: 0 - 1000 ± 5 1000 - 2500 + 5 / - 15 2500 + ± 1.5 % ALL DIMENSIONS IN mm UNLESS OTHERWISE SPECIFIED This drawing remains the property of ECEFast. It is subject to recall, and must not be reproduced in part, or in whole, or its contents passed to third parties without prior written consent.
CKD	DR	12/05/09	
DWN	TD	12/05/09	
NAME	DATE		

1800 811 818 MELBOURNE
 www.ecefast.com.au SYDNEY
 BRISBANE
 GLADSTONE (QLD)
 0 800 ECE FAST AUCKLAND (NZ)
 www.ecefast.co.nz

TEMP SENSOR
 TYPE Pt100
 AIR TEMP PROBE
 NO PROCESS FITTING

TS-51P-CAT	
ECE Dwg No.	
0	Units: mm
Revision:	Scale: NTS