



STANDARD CONSTRUCTION

- Element is Pt2100, Band 1, 260°C, 3-wire as ② standard. Please specify variations if required.
- Std operating temperature range is -50°C to 260°C
- Cold junction is rated to 100°C
- Connector block is bakelite (ceramic optional)
- Process fitting is 1/2" BSPT
- Duplex construction (6 wires total)
- Sheath is 316 grade stainless steel

ADDITIONAL REQUIREMENTS

If variations from the standard construction, or additional features are required, please specify.

Options include:

- Different RTD element
- Transmitter fitted
- Different temperature range
- Vibration proof
- High temperature cold junction requirements

3	DR	10/08/07	DIAMETER STANDARD 4.7 WAS 4.5
2	DR	18/05/07	Pt2100 WAS 2 x Pt100 TOLERANCES ADDED TO BORDER DETAIL
1	GC/DR	SEPT 06	RE-DRAWN & RE-ISSUED

APP	R.G	JAN 05	STANDARD TOLERANCES: 0 - 1000 ± 5 1000 - 2500 + 5 / - 15 2500 + ± 1.5 % ALL DIMENSIONS IN mm UNLESS OTHERWISE SPECIFIED
CKD	G.C.	NOV 04	
DWN	C.L.	MAR 04	
NAME	DATE		

1800 811 818
www.ecefast.com.au

ECEFast 0 800 ECE FAST
www.ecefast.co.nz

MELBOURNE
SYDNEY
BRISBANE
GLADSTONE (QLD)
AUCKLAND (NZ)

TEMP SENSOR
 MODEL TS-15P (duplex)
 1/2" BSP PROCESS FITTING
 LARGE HEAD

TS-15P-CAT	
ECE Dwg No.	3
Revision:	3
	Units: mm Scale: NTS