

<p><b>Right Angle Flat Surface Probe</b> 50001 (J,K or T)</p>	<p>Max Temp Tip: 400°F (205°C) Max Temp Cable: 400°F (205°C) Response Time: 7 seconds, oiled surface Flexible Armored Cable</p>	
---	---	--

<p><b>Weighted Griddle Surface Probe</b> 50014 (J,K or T)</p>	<p>Max Temp Tip: 500°F (260°C) Max Temp Cable: 400°F (205°C) Response Time: 2 seconds, oiled surface Flexible Armored Cable</p>	<p>Weighted probe allows hands-free use.</p>
---	---	--

<p><b>Moving Surface Bow Probe - Replaceable Sensor</b> 50069 (J,K or T)</p>	<p>Max Temp Tip: 500°F (260°C) Max Temp Cable: 221°F (105°C) Response Time: 4 seconds, oiled surface Replaceable Sensor: MD 3132-10 (Type K); MD 3132-8 (Type J) MD 3132-12 (Type T) Flexible Cable with PVC Jacket</p>	<p><b>Moving Surface Probe</b></p> <p>Designed for moving surfaces and rollers. Gives a more accurate measurement on moving surfaces than a standard surface probe.</p>
--	---	---

## MISCELLANEOUS PROBE DESIGNS

All measurements are stated in inches or feet followed by the metric equivalent in parentheses.

<p><b>Combo Probe 50701-K</b></p>	<p>Max Temp Tip: 500°F (260°C) Max Temp Cable: 400°F (205°C) Response Time: 2 seconds, liquid Flexible Cable with Viton® Jacket Type K only</p>	<p><b>Combo Probe</b></p> <p>The Combo probe is ideal for measuring meat combos, large cooking kettles &amp; vats, and compost.</p>
-----------------------------------	---	---

<p><b>Bare Tip Probe, - Teflon® Cable 39138 &amp; 50416 (J,K or T)</b></p>	<p>Max Temp Tip: 400°F (205°C) Response Time: 1 second, liquid; 7 seconds, in 5m/sec. air Flexible Cable with Teflon® Jacket</p>	<p><b>Bare Tip Probes</b></p> <p>Bare thermocouple junctions can measure immersion or air temperatures, or can be installed in substrates of surfaces. Can be embedded in products for freezing and heating studies.</p>
--	--	--



www.cooper-atkins.com