

# CO<sub>2</sub> / RH / Temperature CO / O<sub>2</sub> / Wet bulb Selection guide

## Hand held meters



Model	<a href="#">LU-GCH-2018</a>	<a href="#">LU-AQ9901SD</a>	<a href="#">LU-MCH-383SD</a>
Measured Parameters	Three values: CO <sub>2</sub> , Temperature, Humidity; Dew point is calculated automatically from Humidity/Temp value	Six values: CO <sub>2</sub> , CO, O <sub>2</sub> , Temperature, Humidity and Dew point; Dew point and wet bulb values are calculated automatically from Humidity/Temp value	Three values: CO <sub>2</sub> , Temperature, Humidity
Number of probes	Two (CO <sub>2</sub> /Temp) & (Humidity/Temp)  At a time, only one probe can be connected to the meter	Four CO <sub>2</sub> /Temp probe CO/Temp probe O <sub>2</sub> /Temp probe and Humidity/Temp probe All 4 probes can be connected at the same time	One CO <sub>2</sub> probe
Display	CO <sub>2</sub> / Temp or Humidity/Temp. Any one of the two pairs	One parameter at a time together with temperature	CO <sub>2</sub> /Humidity/Temp, all three values at the same time
Range	CO <sub>2</sub> 0 ... 4,000 ppm Temperature 0 ... 50°C Humidity 10% ... 95% Dew point temp -25.3°C ... 48.9°C Wet bulb temp CO O <sub>2</sub>	0 ... 4,000 ppm 0 ... 50°C 5% ... 95% -25.3°C ... 48.9°C -21.6°C ... 50.0°C 0 ... 1,000 ppm 0 ... 30%	0 ... 4,000 ppm 0 ... 50°C 10% ... 95%
Data logging	No	Yes 3 probe's data can be recorded simultaneously. (%RH/CO <sub>2</sub> /O <sub>2</sub> /Temp) or (%RH/CO <sub>2</sub> /CO/Temp)	Yes
Power supply	Either 6 x 1.5V AA battery or through the power adapter (AC/DC 9V)	Either 6 x 1.5V AA battery or through the power adapter (AC/DC 9V)	Through the power adapter (AC/DC 9V)

**Please note:** While using CO<sub>2</sub> sensor it is advisable to use the power adapter as the power consumption is approximately DC 136.5mA compared to Humidity sensor which is DC 10.5 mA

CO<sub>2</sub> guideline for different environment like office work place, home, school, hotel, public area, indoor swimming is ≤ 1,000 ppm. The minimum temperature acceptable for the working environment is 18°C. RH level below 50% is ideal and will help to prevent dust, mould, condensation etc.,