

RC-5+



weblink

Model	Description	Price
TC-TS20TL5P	RC-5+ USB Temperature logger with internal sensor Temperature range -30°C ...+70°C Resolution 0.1°C Accuracy ±0.5°C (-20°C ...+40°C) others, +1°C Record capacity 32,000 points (MAX) Sensor Internal NTC thermal resistor Features Immediate start & timing start mode, Multi-alarms Recording interval 10 sec to 11:59:50 (H:M:S) Battery CR2032 (replaceable)	\$96.00
TC-TS20TL5PEX	External probe (optional) NTC thermal resistor Response time: with external probe 30 seconds	\$38.00
RC-5+ loggers are equipped with an integrated USB port and generate a PDF report automatically, so they do not require any additional software to read the data. However, the Data Management (free downloadable software) allows you to configure the device according to your needs and manage the data comfortably from your PC.		

DISKLOG



weblink

EC-DISKLOG	Logger with disk and chain Temperature range -30°C ...+85°C Resolution 0.5 °C Accuracy ±1.0°C (-5°C ...+85°C) Record capacity 2048 points (MAX) Recording interval 1 to 255 minutes Battery 3.0V lithium (non- replaceable)	\$96.00
EC-DISKLOG-BARE	Bare logger Logger button only (no disk and chain)	\$59.00
EC-DISKLOG-RH/T	Logger for RH & Temp , 2000 points, 0-100%RH/-20...85°C	\$268.00
EC-DISK-ETEMPLT	DISKLOG S/WARE + USB Interface	\$215.00
EC-DISK-KIT-USB	Kit: USB interface + Windows 7 or 10 software + 1 x Temperature logger	\$298.00
Battery Life 5 years based on 20 min log rate at +15°C: PC programmable, economical, extra heavy-duty, Hi/Lo Alarms optional RH with easy to use software		

LogTag



weblink

EC-LOGTAG-TEMP	LogTag recorders with internal sensor Temperature range -40°C ...+85°C Resolution 0.1°C(-40...+40°C),0.2°C(40...+80°C) Accuracy ±0.5°C ... ±0.8°C Record capacity 16,000 readings Recording interval 1min to several hours Battery 3.0V lithium (non- replaceable)	\$89.00
EC-LOGTAG-1EH	LogTag for temperature with plug in external probe	\$198.00
EC-LOGTAG-RH/T	LogTag for RH and temperature with internal sensor	\$174.00
EC-LOGTAG-PROBE	LogTag external probe only	\$98.60
EC-LOGTAG-INT/S	LogTag USB interface and LogTag Analyzer software is freely downloadable	\$169.00

Prices mentioned are in NZD and doesn't include GST.

EVT2

[weblink](#)

Model	Description	Price
KM-EVT2	Temperature logger with Display – Comark Temperature range -30°C ...+70°C Resolution 0.1°C System accuracy ±0.5°C Memory 3000 readings (MAX) Recording interval 1sec to 99 hours Sensor Thermistor (integral) Battery ½ AA lithium (non- replaceable)	\$169.00
KM-EVTCRU	Interface docking station includes interface. Free downloadable software	\$65.00
KM-EVT2-KIT	Starter kit: Includes logger, docking station & interface	\$224.00
Battery Life 24 months based on 15 min log rate at +20°C with alarms off Case Material - Food Safe polycarbonate		

CE-340/342

[weblink](#)

CE-340	Temperature logger with display - Center Temperature range -30°C ...+70°C Resolution 0.1°C Accuracy ±0.7°C Record capacity 64,000	\$149.00
CE-342	Humidity and temperature logger with display Humidity range 5% ...98% Resolution 0.1°C Accuracy ±0.7°C Record capacity 32,000 each RH and T	\$199.00
CE-340/345	Temperature logger kit	\$219.00
CE-342/345	Humidity and temperature logger kit	\$ 269.00
Kit includes logger with RS232 cable, software and CE-345 hanger (docking station) Replaceable battery 1.5V AAA x 2		

LU-MTM-380SD

[weblink](#)

LU-MTM-380SD	Temperature logger for type K thermocouple with display Temperature range -100°C ...+1300°C Resolution 0.1°C Accuracy ±0.5°C Record capacity Logging in SD card 1GB...16GB max Recording interval 5 ... 600 seconds	\$225.00
3 channels data logger. Recorded data can be downloaded to excel spread sheet, no extra software required, Replaceable battery 1.5V AAA x 6 or 9VDC adapter in;		

LU-MCH-383SD

[weblink](#)

LU-MCH-383SD	Humidity, temperature & CO₂ data logger with display Temperature range 0 ...+50°C CO ₂ range 0...4000ppm RH range 10...90% Record capacity Logging in SD card 1GB..16GB max Recording interval 5 ... 600 seconds or Auto	\$418.00
Meter's power supply is from 9VDC power adapter (240VAC to 9 VDC power adapter included with the meter). 1.5 V AAA batteries are only for the clock time base backup. The " Auto " sampling means the data will be saved only when the measuring value is changed (> ± 1 %RH or > ± 1 °C or ± 50 ppm)		

Prices mentioned are in NZD and doesn't include GST.

CH-TS13PRD

[weblink](#)

Model	Description	Price
CH-TS13PRD <i>DiskInterface HS</i>	Autoclave Pressure & temperature datalogger	2,989.00 429.00
Temperature	Range -40°C ...+140°C Resolutio 0.02°C Accuracy ±0.1°C	
Pressure	Radial 20mm length x 3 Ø mm Range 0 ... 5 bar A Resolutio 2 mbar Accuracy ± 15 mbar	

Food grade material, IP68; Data acquisitions at 1 second step; Dimensions: 55mm H X 35 Ø (mm), with ½ Gas threaded part; managed with Windows software and USB interface. Accredia traceable calibration certificate is included for points: 25/50/75/100/125/140°C; 10/1k/2k/4k mbar). Requires *DiskInterface HS* to communicate with *HumiPressureDisk* to program and download the data. *HumiPressureDisk* software is freely downloadable and *TS Manager* is licensed

CH-SterilDisk

[weblink](#)

SterilDisk series features different data logger version for temperature up to 140°C, for thermal processes such as sterilisations, pasteurisation, cooking etc. SterilDisk comes with internal sensor or with 10 mm, 20 or 50 or 100 or 150mm external probe up to 140°C, managed with Windows software and USB interface. Probes cannot be switched. Accredia traceable calibration certificate is included for standard calibration points: 25/50/75/100/125/140°C. Requires minimum *DiskInterface HS* or *DiskInterface HS Mini* to communicate with *SPD* or *TS Manager* software. **Please call us or email us for a quote**

**CH-TS01SMD
CH-TS01PMD**

[weblink](#)

CH-TS01SMD S-Micro	S-Micro temperature datalogger	1,854.00
	Data logger 0°C ...+140°C Probe 0°C ...+220°C	
CH-TS01PMD P-Micro	P-Micro temperature datalogger	1,754.00
	Temperature 0°C ...+100°C	

Base 14 H x 17 Ø mm, probe 20/50/100/150 l x 3 Ø mm, for other lengths contact us. Resolution is 0.01°C & accuracy is ± 0.1°C. Accredia traceable calibration cert is included for calibration points: 25/50/75/100/125/140°C. Managed through *SPD* or *TS Manager* software (compatible with FDA 21 CFR Part 11 regulation) & interface *DiskInterface HS* or *DiskInterface HS Mini*. **Call us for a quote.**

**S-Micro L/XL
P-Micro L/XL**

[weblink](#)

S-Micro L/XL and P-Micro L/XL: Pasteurisation and sterilisation data logger		
S-Micro L/XL	Logger temperature -40°C to +140°C Probe temp range -40°C to +220°C	945.00
P-Micro L/XL	Probe temp range -40°C to +100°C	845.00
Dimensions for L/XL 39 H X 17Ø / 64 H X 17 Ø		

Probe dimension 20/50/100/150 l x 3 Ø mm, for other lengths contact us. Managed through *SPD* (freely downloadable) or *TS Manager* (compatible with FDA 21 CFR Part 11 regulation) software and the interface *DiskInterface HS* (\$429) or *DiskInterface HS Mini* (\$250). Resolution is 0.01°C, Accuracy is ±0.1°C. Accredia traceable calibration certificate is included for standard calibration points

Prices mentioned are in NZD and doesn't include GST.