

**CE-521**

[weblink](#)

## Wireless 4 channel data logger

Model No	CE-521 (Thermometer only-probes not included)	\$ 394.00
Functions	Bluetooth wireless real-time monitor; Micro USB PC interface; T1-T2 function; MIN/MAX/AVG; Data logging up to 32000 records each channel; Recall function to instantly read-out up to 100 sets manually saved data	
Temperature range	-200 ~ 1370°C (K-type)	
Accuracy/ Resolution	±0.1% + 0.7°C/0.1°C	
Sample rate	0.5 sec/channel	
CE-521 supports K, J, E, T, N, R, S types of thermocouple probes with large backlit LCD screen; Supplied as kit with software cable, software, Bluetooth adapter <b>BT-01</b> and carry case.		

## HACCP Auditor data management system

**KM-N5001**

[weblink](#)

Model No	KM-N5001-KIT (Auditor unit+software+interface+probe) \$ 935.00	
Functions	Log, monitor and manage data. User friendly program virtually any critical control check to suit HACCP or due diligence plan. Flexible recording and reporting throughout the supply chain; Full security with controlled authorised user access	
Probe	Supports K and T type Probes with 6-Pin Lumberg	
Display	Full graphic display LCD, 128 x 64 pixels with 0.1°C resolution	
Power supply	2 x 1.5V AA battery	
KM-N5001 minimises risk of human error, eliminates paper records, fully programmed using Auditor software to provide flexibility and recording functions of palm hand held organisers. IP67, micro USB connection to PC, free consultation to programme the auditor.		

## HACCP Touch HT100 data recorder

**KM-HT100/PK19**

[weblink](#)

Model No	KM-HT100/PK19	\$ 499.00
Functions	Simple paperless HACCP recording, easy to navigate touchscreen interface, fully programmed to record information on all critical events in HACCP plan, record tasks, temperatures and corrective actions and cleaning checks. Data export in PDF format.	
Temperature range	-73 ~ 537°C (K-type)	
Display	3" four colour resistive touch screen	
Storage capacity	6500 recording and 100 files	
Power supply	Lithium polymer battery rechargeable via micro USB cable (included)	
HT100/PK19 comes with K type probe. (T type probe is optional); Features an easy-to-read touch screen and a hard-wearing rubber boot. Download reports as Excel or PDF		

## Blue2, Bluetooth thermometer

**AT-20100-K + AT-50207K**

[weblink](#)

Model No	AT-20100-K + AT-50207K	\$ 619.00
Functions	AT- 20100-K Blue2 Instrument and 50207-K Needle Probe form a matched pair. Temperature data is transmitted wirelessly to your mobile device via Bluetooth Low Energy. The data can be integrated into existing third-party application	
Temperature range	-40 ~ 537°C	
Resolution	0.1°C	
Accuracy	±0.3°C, at ambient temp between 20°C to 30°C	
RF Range	100 ft, line-of-site	
Power supply	3V Lithium (CR123A) 500 hours	
The Blue2 can utilize any interchangeable Type-K thermocouple temperature probe, making it versatile for insertion, air or surface temperature measurement.		

Prices mentioned are in NZD and doesn't include GST.