

Infrared thermometers

FK-62MAX/FK-62MAX+


Adjustable emissivity
(0.1 to 1.0);
Response:
500msec/300msec;
Accuracy: $\pm 1.5^{\circ}\text{C}$ /
 $\pm 1.0^{\circ}\text{C}$

CH-AZ-BG32


Emissivity fixed@0.95,
Resolution: 0.5°C ,
Accuracy: $\pm 2^{\circ}\text{C}$ or 2%
Soft pouch included

CH-AZ-BG48


10-point memory,
Audible alarms,
Resolution: 0.1°C ,
Accuracy: $\pm 2^{\circ}\text{C}$ or 2%

CH-AZ-TNCOMBO-C


Resolution: 0.2°C ,
Accuracy: $\pm 1^{\circ}\text{C}$ or 1.5%

FK-64MAX


99 data point memory
Response: 500msec
Repeatability: $\pm 0.5\%$ or
 $\pm 0.5^{\circ}\text{C}$; Flash light
Resolution: 0.1°C
Accuracy: $\pm 1^{\circ}\text{C}$ / $\pm 1\%$

KM-FOODPRO


Resolution: 0.1°C ,
Accuracy: $\pm 1^{\circ}\text{C}$, Soft
pouch included


CH-LASERTEMP

Emissivity fixed@0.95,
Resolution: 0.1°C ,
Accuracy: $\pm 2^{\circ}\text{C}$ or 2%,
Circular laser

Model No	Temp range	D:S	Price*
CH-AZ-BG32	-20 to $+320^{\circ}\text{C}$	8:1	169.00
CH-AZ-BG48	-20 to $+1000^{\circ}\text{C}$	50:1	449.00
CH-AZ-TNCOMBO-C	-55 to $+250^{\circ}\text{C}$	12:1	190.00
CH-LASERTEMP	-30 to $+500^{\circ}\text{C}$	9:1	85.00

Model No	Temp range	D:S	Price*
FK-62max	-30 to $+500^{\circ}\text{C}$	10:1	229.00
FK-62max+	-30 to $+650^{\circ}\text{C}$	12:1	270.00
KM-FOODPRO	-30 to $+200^{\circ}\text{C}$	2.5:1	248.00
FK-64MAX	-30 to $+600^{\circ}\text{C}$	20:1	299.00

*Prices mentioned are in NZD and doesn't include GST.

Click the respective model number at the table for more details and to place the order in website

Infrared & contact thermometers
TK-TNCOMBO


Resolution: 0.2°C,
Accuracy: ±1°C or 1.5%
Kit comes with TS-TP05,
Type K thermocouple
probe with carry case

KM-FOODPROPLUS


Accuracy: ±1°C or ±1.5%
High brightness LED indication
Resolution: 0.1°C above 0°C &
1°C below 0°C
Retractable RTD sensor

CH-AZ-TCT303-C


Accuracy: ±1°C
Adjustable emissivity
Max/min/lock function
White LED indication
Resolution: 0.1°C above
0°C & 1°C below 0°C
Retractable probe

FK-561


Accuracy: ±1°C / ±1%
Response: 500msec
Repeatability: ±1°C
Resolution: 0.1°C

FK-566/FK-568


Accuracy: ±1°C / ±1%
Response: 500msec
Resolution: 0.1°C
Type K thermocouple input,
20 memories/99 memories
Hi/Lo visual & audible alarm

FK-572-2


Professional new version
Accuracy: ±1°C or 1%,
Resolution: 0.1°C,
Max/min/Diff/Average
99point data storage
Type K thermocouple input
Dual laser sight, trigger lock

Model No	IR Temp range	D:S	Price*
TK-TNCOMBO	-55 to +250°C	12:1	275.00
CH-AZ-TCT303-C	-50 to +250°C	2.5:1	178.00
KM-FOODPROPLUS	-35 to +275°C	2.5:1	354.00

Model No	IR Temp range	D:S	Price*
FK-561	-40 to +550°C	12:1	483.00
FK-566	-40 to +650°C	30:1	909.00
FK-568	-40 to +800°C	50:1	1196.00
FK-572-2	-30 to +900°C	60:1	2048.00

**Prices mentioned are in NZD and doesn't include GST.*

Click the respective model number at the table for more details and to place the order in website

Contact thermometers



Connector: Lumberg(C21)
Sub-miniature(C26/C28K)

Suggested 3x100mm penetration probes: KM-PX22L(C21): \$135,
TS-TP05-T: \$59; TS-TP05: \$59



Single channel K type T/C input, 2 & 4 channel models available.
Comes with bead probe & carry case

CH-HACCP THERM



Measuring range of the probe:
Max 150°C

Probe included

AT-35132/35135



Probe included with the thermometer. Both DuraNeedle (35132) & Bell surface probe (35135) uses the same AquaTuff™

KM-C22



Accepts both T type T/C and thermistor probe. **Suggested 3x100mm penetration probes:** KM-PX22L(thermistor): \$135, KM-PT24L(T type T/C): \$140

Model No	Temp range	Sensor type	Price*
KM-C21	-50 to +150°C	Thermistor	199.00
KM-C26	-200 to +400°C	T Type T/C	248.00
KM-C28K	-200 to +600°C	K Type T/C	360.00
CH-HACCP THERM	-40 to +300°C	4x150mm probe incl.	88.00

Model No	Temp range	Sensor type	Price*
CE-300	-200 to 1370°C	K Type T/C	119.00
AT-35132	-73 to 260°C	K Type T/C	457.00
AT-35135	-73 to 260°C	K Type T/C	497.00
KM-C22	-50 to +150°C / -200 to +400°C	Thermistor/ T type T/C	339.00

*Prices mentioned are in NZD and doesn't include GST.

Click the respective model number at the table for more details and to place the order in website
Please add the matching probes for the thermometers. Click here for [probe options](#) in our website

Pocket thermometers

KM-PDQ400


Reduced tip: 1.5mm
Field calibratable
Side display
1.5 V Button cell

AT-DFP450W


Reduced tip: 1.5mm
120mm stem
Top display
1.5 V Button cell

KM-DT400


Reduced tip: 1.5mm
Field calibratable
Top display
1.5 V Button cell

CH-AI368


Reduced tip: 1.5mm
70mm stem
Side display
1.5 V Button cell

CH-ST9212B


97mmx 3mm stem
Side display
1.5 V Button cell

Model No	Temp range	Resolution	Accuracy	Response	Min/Max /Hold	Price*
KM-PDQ400	-20 to +200°C	0.1°C	±0.5°C	< 6 sec	Max	55.00
AT-DFP450W	-40 to +232°C	0.1°C	±1.0°C	< 6 sec	All	55.00
KM-DT400	-20 to +200°C	0.1°C	±0.5°C	< 6 sec	Max	55.00
CH-AI368	-40 to +200°C	0.1°C	±1.0°C	< 6 sec	All	35.00
CH-ST9212B	-50 to +150°C	0.1°C	±1.0°C	1 sec	All	32.90

**Prices mentioned are in NZD and doesn't include GST. Price includes 1 point (0 or 80°C or 100°C) traceable calibration certificate which will be issued at the request. Click the respective model number at the table for more details and to place the order in website*