



Weblink 62

Weblink 64

Model	Fluke 62 Max	Fluke 62 Max+	Fluke 64 Max
Range	-30 to +500°C	-30 to +650°C	-30 to +600°C
Response time	< 500 ms	< 300 ms	< 500 ms
Optical resolution	10:1	12:1	20.:1
Display resolution	0.1°C		
Emissivity	0.10 to 1.00 adjustable		
Accuracy	±1.5°C	±1.0°C	±1.0°C
Power	AA alkaline battery		
Special function	Single Laser spot	Dual Laser sighting	Single Laser spot. 99 data memory
Price	219.00	270.00	299.00



Weblink

Model	FoodPro	FoodPro Plus
Range	-30 to +200°C	-30 to +275°C
Response time	< 500 ms after initial reading	
Optical resolution	2.5:1 @ 90 % energy, typical	
Display resolution	4 digits, 0.1°C resolution	
Emissivity	Pre-set for foodservice applications	
Accuracy	±1.0°C > 65; ±1.5°C < 65	
Power	AA alkaline battery	9 V alkaline battery
Special function	-	Foldable RTD probe
Price	248.00	354.00



Weblink

Weblink

Model	CH-AZ-BG32	CH-AZ-BG48
Range	-20 to +320°C	-32 to +1000°C
Emissivity	Fixed at 0.95	0.10 to 1.00 adjustable
Optical resolution	8:1	50:1
Accuracy	±2.0°C	±2.0°C >100°C ±2% <100°C
Power	9 V alkaline battery	
Special function	Selectable laser sighting	
Price	169.00	449.00



Weblink

Weblink

Model	BG45	TK-TNCOMBO	TNCOMBO
IR Range	-60 to +500°C	-55 to +250°C	
Accuracy	±2.0°C	±1.0°C > 65; ±1.5°C < 65	
Optical resolution	11:1	12:1	
Emissivity	0.10 to 1.00 adjustable		
Power	AA alkaline battery		
Special function	K type probe (optional)	K type probe included	-
Price	196.00	240.00	190.00

Prices mentioned are in NZD and doesn't include GST

Click the respective link for more details and to place the order in website

Infrared thermometers



[Weblink](#)

Model	Fluke 566	Fluke 568
Range	-40 to +650°C	-40 to +800°C
Response time	< 500 ms	
Optical resolution	30:1	50:1
Display resolution	0.1°C resolution	
Emissivity	0.10 to 1.00 by 0.01	
Accuracy	±1.0°C or ±1.0% whichever is greater	
Power	2 x AA alkaline battery	
Special function	Single-point laser; K-type probe optional; data storage	
Price	939.00	1,241.00



[Weblink](#)

Model	Fluke 561	Fluke 572-2
Range	-40 to +550°C	-30 to +900°C
Response time	500ms	< 500 ms
Optical resolution	12:1	60:1
Display resolution	0.1°C resolution	
Emissivity	3 settings: 0.3/0.7/0.95	0.10 to 1.00 by 0.01
Accuracy	±1.0°C or ±1.0% whichever is greater	
Power	2 AA alkaline battery	
Special function	Single-point laser	K-type probe, memory
Price	483.00	2,048.00



[Weblink](#)



[Weblink](#)

Model	TCT303	KM-814FS
Range	-50 to +250°C	-30 to +200°C
Optical resolution	2.5:1	4: 1
Display resolution	0.1°C resolution	0.5°C resolution
Emissivity	Adjustable	Pre-set at 0.97
Accuracy	±1.0°C	±1.0°C
Power	2 AAA battery	9V alkaline battery
Special function	Foldable TC probe	Hold function
Price	178.00	189.00



[Weblink](#)



[Weblink](#)

High temperature Raytek® Ranger 3i Plus is designed for use in high-temperature applications, 400°C to 3000°C, such as furnaces, heat treatment and power plants.

ECEFast NZ Ltd is a direct wholesale outlet to deliver well-known brands to New Zealand customers at competitive prices.

Our calibration service has a proven track record with experienced calibration technician. Call us to book your new or existing thermometers to get it calibrated.

Prices mentioned are in NZD and doesn't include GST

Click the respective link for more details and to place the order in website